N4301/AL numeric keypad access control kit

Reference: N4301/AL
Product code: 11884301
EAN code: 8429898014326



Main characteristics

Stand alone access control kit through numeric keypad.
Composed of:

- N3301/AL access control module.
- N6001/AL assembling set.
- NCEV-90CS embedding box.
- TF-104 transformer.
- CV-14 12V a.c. lock release.

More information

- Front of 1.8mm. thick anodized extruded aluminium.
- Backlit numeric keypad with stainless steel covered push buttons
- Selectable acoustic acknowledgement signal on push.
- Light status indication.
- Removable terminal connector for easy wiring.
- Tamper alarm.
- 2 relay outputs (N/C or N/O) with independent remote activation input and panic output (12Vd.c.).
- Remote activation inputs can be enabled / disabled through a programmable code.
- Programmable activation time (1 to 99 sec.) and output mode (single shoot or stable).
- 1,000 codes of 4, 5 or 6 digits. Each code can be programmed to activate a combination of outputs.
- User codes and special codes can be changed without the need to enter into programming mode.
- Access control can be disabled during a period of time after the introduction of a number of wrong consecutive codes.
- Tamper alarm.
- 12V a.c. or 18 to 24V d.c. power input.
- Dimensions:
  - External: 128(W) x 153(H) mm.
  - Embedded: 99(W) x 133(H) x 56(D) mm.

Kit composed of:
N3301/AL access control module.
N6001/AL assembling set.
NCEV-90CS embedding box.
TF-104 transformer.
CV-14 12V c.a. lock release.

Visit in the website: https://www.golmar.es/products/n4301-al

Golmar Sistemas de Comunicación S.A.
Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • golmar@golmar.es • www.golmar.es

N4301/AL numeric keypad access control kit

Specifications	
Type Function	Standalone
Reading / Detection Type	PIN
Use	Outdoor,Indoor
Mounting	Embedded
Relay contacts	No
State LEDs	Yes
Dimensions - High (mm)	133
Dimensions - Width (mm)	99
Dimensions - Deep (mm)	56
Weight (gr.)	1500

Accessories

- N871/AL surface box with integrated rain shield

Visit in the website: https://www.golmar.es/products/n4301-al

Golmar Sistemas de Comunicación S.A.
Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • golmar@golmar.es • www.golmar.es