C5110/EDGE 7W/G+ one line video kit with Wifi call forwarding

Reference: C5110/EDGE 7W/G+
Product code: 12305113
EAN code: 8429898032351



Main characteristics

CLIP IP G+ video door panel kit with call forwarding via Wi-Fi

- CLIP/G+ door panel with 1 call button.
- Monitor EDGE 7W/G+ 7" hands free:
  - **Integrated Wi-Fi**
  - **Compatible with Alexa and Google Home**
  - **Image Memory**
- PoE Switch SW-104M

More information

MONITOR EDGE 7W/G+

- Hands-free monitor for surface mounting in white finish
- 7" capacitive touchscreen
- High-efficiency speakers
- Secure audio, video and door-opening communications
- Spy camera, auto-on, Doctor mode and Do Not Disturb functions
- Voicemail function, so it can store a message if you do not answer
- Selective intercom communication with other units in the apartment
- Customisable ringtones
- Customisation of the monitor's background
- Connection to the doorbell push-button, eliminating the need to use the doorbell
- Auxiliary chime output
- Image memory, storing photos or videos in internal storage (SD card option for extended memory)
- Easy pairing of the monitor with the G2Call+ app via on-screen QR code

Dimensions: 179 (W) x 116 (H) x 21 (D) mm.

G2CALL+ APP
This monitor allows calls to be forwarded to the G2Call+ App, adding the following features:

- Call forwarding and auto-switch-on function via the app
- Remote door opening
- Door opening via QR codes generated by the app
- Integration with Alexa
- Integration with Google Home
- Viewing of CCTV cameras linked to the monitor

KIT C5110/EDGE 7W/G+
Switch PoE 104-M
Up to 6 monitors in the same home.
Door opener not included. Recommended:
CV-14P/UNI/SF (20600155)
CV-24P/UNI/SF (20600253)
CV-16P/UNI/SF (20600160)
CV-26P/UNI/SF (20600158)

CLIP PANEL

- Graphite coloured Zamak alloy housing
- Black coloured acrylic front
- **2MPx** CMOS camera with **150º** wide angle optics
- **IK07** anti-vandalism and **IP65** weatherproof rating
- **Prompt messages** and call button with **SmartPrompt**' luminous indication of the different system statuses
- **13.56MHz** RFID proximity reade supporting up to 2,000 cards, with Wiegand26 and RS485 outputs
- Door opening via **QR codes** (exclusively with Wi-Fi monitors)
- 12Vdc output for activating one door
- Designed for use with 12 Vdc electric door strikes
- Compatible with 48V PoE switches and connection via RJ-45 connector, with the option of local 12 Vdc power supply
- Surface mounting with rain shield included

Dimensions: 70(W) x 170(H) x 27(D) mm

Accessories

- RC-EDGE METAL mounting bracket
- SOB-UNI table stand
- RC-EDGE-SUP METAL mounting bracket

Visit in the website: https://www.golmar.es/products/c5110-edge-7w-g-plus-one-line-video-kit-with-wifi-call-forwarding

Golmar Sistemas de Comunicación S.A.
Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • golmar@golmar.es • www.golmar.es