BIO-N reader for Supra panels

Reference: S3000/BIO-N/AL
Product code: 12583315
EAN code: 8429898032894



Main characteristics

- Stand-alone access control module with fingerprint and 125KHz reader
- Capacitive fingerprint sensor
- Wiegand 26 output for connection to access control panels
- Light and acoustic indicator of operation
- Up to 899 user cards and 99 fingerprints
- Optional access control blocking after 10 consecutive wrong fingerprint entries
- Compatible with PROKEY ID cards and TAGKEY ID key fobs
- 1 relay output (NO, C, NC) for door, with input for remote activation
- Programmable activation time (1 to 99 seconds) and output mode (pulse or steady)
- Tamper alarm
- 12 or 18V d.c. power supply
- 1 height

More information

Specifications	
Technology	wiegand
Type Function	Standalone,Slave
Reading / Detection Type	Proximity,Fingerprint
RFID Frequency (KHz)	125
RFID Reading /coverage distance (cm)	7
Use	Outdoor,Indoor
Max. Users	1000
Signaling	Led
Display	No
Expandable	No
Antenna	No
Relay contacts	Yes
Incorporates base	No
Incorporates cover/front panel	Yes
State LEDs	Yes
Input voltage	12Vdc,18Vdc
Powered by controller	Yes

Accessories

- PROKEY ID proximity card
- PSU-121B 12Vdc / 1.3A power supply
- TAGKEY ID proximity key fob

Visit in the website: https://www.golmar.es/products/s3000-bio-n-al

Golmar Sistemas de Comunicación S.A.
Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • golmar@golmar.es • www.golmar.es